

4K UHD LED
PROFESSIONAL MONITOR

Our newly developed 27.89" & 39.5" professional monitors featuring a full 4K 3840 x 2160 resolution. These monitors accept 4K signals at the multiple various video interface, Display port / 60p, HDMI / 30p, DVI-D / 30p also accept full SDI signal & VGA up to 1920 x 1080 / 60p for various application use.



4K ULTRA HI-DEFINITION

SPECIAL FEATURES

- High Contrast 3840 x 2160 Resolution Panel with LED Backlight
- Anti-Reflection Front Coating
- Full 60fps Frame Rate (Display Port)
- Multi-Input Interface: Display Port, HDMI, DVI-D, SDI, VGA
- Wide Viewing Angle
- Industrial Grade Metal Cabinet
- Multi Display Function (PIP / PBP)
- Height Adjustable Stand (4K28DHD)

PRODUCT VIEW

Our 4K UHD professional monitor is designed sleek and thin bezel exterior with Electro Galvanized Steel chassis to support in any environment.



Front View



Side View

SPECIFICATION

SERIES	4K28DHD LED	4K40DHD LED
DISPLAY		
Screen Size	27.89 Inch	39.5 Inch
Native Resolution	3840 x 2160 pixels	3840 x 2160 pixels
Pixel Pitch	0.16 x 0.16 mm	0.2247 x 0.2247 mm
Brightness	300cd/m ²	350cd/m ²
Display Color	1.07 Billion	1.07 Billion
Contrast Ratio	1000 : 1	5000 : 1
Aspect Ratio	16 : 9	16 : 9
Viewing Angle (H/V)	170° / 160°	176° / 176°
Response Time	< 5.0ms	< 8.5ms
Video System	NTSC / PAL	NTSC / PAL
INTERFACE		
Display Port In (ver. 1.2)	1	1
HDMI In (ver. 1.4)	1	1
DVI-D In (Dual)	1	1
3G-SDI In / Out	1 / 1	1 / 1
Audio In	1 (for VGA & DVI)	1 (for VGA & DVI)
Audio Out	1	1
VGA In (15Pin D-Sub)	1	1
SPEAKER		
Built In Speaker	Yes	Yes
TRANSMITTER		
IR Remote Control	Yes	Yes
FEATURES		
Multi Display Function	Yes	Yes
Deinterlacing	Yes	Yes
Noise Reduction	Yes	Yes
Multi Language	English	English
CABINET		
Color	Black	Black
Base Stand	Desktop Stand (Height Adjustable)	Desktop Stand
Material	Electro-Galvanized Steel	Electro-Galvanized Steel
ENVIRONMENT		
Electrical Ratings	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)
Operating Temperature	0° ~ 40° C / 32° ~ 104° F	0° ~ 40° C / 32° ~ 104° F
Storage Temperature	-20° ~ 60° C / -4° ~ 140° F	-20° ~ 60° C / -4° ~ 140° F

* Design and Specifications are subject to change without notice