



ø11 2/3inch F1.6/25mm C				
FOCAL LENGTH		f=25mm		
MAX. DIAMETER (RATIO)		F=1:1.6~16		
ELEMENT		7 GROUPS 9 ELEMENTS		
PICTURE SIZE		6.6x8.8mm	4.8x6.4mm	3.6x4.8mm
ANGLE	VER. ANGLE	15.0°	10.9°	8.2°
	HOR. ANGLE	19.9°	14.6°	10.9°
	DIA. ANGLE	24.8°	18.2°	13.7°
DISTORTION (TV)		-0.01%	-0.02%	0.00%
SHOOTING RANGE AT		VER.	26.3mm	19.2mm
MINIMUM FOCUS		HOR.	35.1mm	25.6mm
DISTANCE		DIA.	43.9mm	32.0mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		11.2mm in air		
FILTER SCREW SIZE		M30.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ø20.0mm		REAR ø13.8mm
MOUNT		C-MOUNT		
EXIT PUPIL		-46.6mm		
TEMPERATURE RANGE		-10~+50° C		
STORAGE TEMPERATURE RANGE		-20~+60° C		
RESOLUTION CENTER/CORNER		CENTER 160本/mm		CORNER 100本/mm
WEIGHT		140 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	承認	八木	製図	大口
		機種名	2/3(ø11) F1.6 f=25mm				
		機種番	LM25JC5M2 外觀図				
2012.03.22	作成年月日						